

Color



Natural Alki | GP2007-N Allyn | GP2008-N

Denny | GP2008-N Madison | GP2006-N



White

Alki | GP2007-W Allyn | GP2008-W Denny | GP2009-W Madison | GP2006-W



Blonde

Alki | GP2007-B Allyn | GP2008-B Denny | GP2009-B Madison | GP2006-B


	North America	Europe
Lamping	Max 15W LED, E26, 120V, not included Optional Integrated LED	Max 15W LED, E27, 220V, not included
Color temperature	2700K (recommended)	2700K (recommended)
Lumen output	Dependent on lamp	Dependent on lamp
Cord	Black, 6.5ft (16ft available) White, 6.5ft (16ft available)	Black fabric, 2m (5m available) White fabric, 2m (5m available)
Canopy	Black powder coated, Ø 4.5, H 3/8 (in)	Black powder coated, Ø 10, H 2.5 (cm)
Material	Recycled corrugated cardboard Corrugated cardboard	Recycled corrugated cardboard Corrugated cardboard
Size	Alki Ø 13, H 8 (in) Allyn Ø 14, H 13 (in) Denny Ø 14, H 25 (in) Madison Ø 22, H 14 (in)	Alki Ø 32, H 19 (cm) Allyn Ø 36, H 32 (cm) Denny Ø 32, H 19 (cm) Madison Ø 56, H 34 (cm)
Weight	1.1lbs 1.5lbs 2.2lbs 2.4lbs	0,5kg 0,5kg 1,0kg 1,1kg
Fire retardant	Yes	Yes
Country of origin	United States	The Netherlands
Certification	CERTIFIED	CE

Dry locations only. Clean with a dry duster or compressed air. Shades are non-toxic, handmade, and manufactured using responsible practices.

Designed in Seattle, Washington, USA.

Custom cords and canopies are available. Contact our offices for more information.





SPECIFICATION CODE


Example: QTY 2 SCRAP - GP2006-B-WHT-6.5-INT

SCRAP - GP

Qty.

1 2 3 4 5

For each number, make one selection and enter into the corresponding box above. *Indicates modification with additional lead time and/or costs



5 LAMPING

E26 E26 Socket
Max 15W LED, E26 base, 120V, not included

INT Integrated LED*
12W COB LED, 0-10v dimming to 1%
80CRI, 120-277V, 2700K